



# AS700 Solar-powered Asset Tracker

The AS700, a solar-powered asset tracker, is ideal for installation on containers, generators, and trailers. With its self-solar power and ruggedized IP69K/IP68 enclosure, it boasts a long lifespan and excels in overcoming environmental challenges. In addition to outdoor GPS tracking, it offers indoor tracking through Wi-Fi positioning and Bluetooth beacons. The AS700 also supports Bluetooth Long-Range connectivity and features motion and tamper detection sensors.



Container



Trailer



Generator



Construction Equipment

## Features

- LTE Cat.1 Connectivity
- Up to 8 years of battery life
- Motion and tamper detection
- Ruggedized IP69K and IP68 enclosure
- Bluetooth Long-Range connectivity for various wireless sensors

## Ordering Information

Model	Region	Connectivity	Power Source	
			Solar Panel	External Cable
AS700-LGCSB-AT02	Global	Cat.1	●	
AS700-LGCSE-AT02	Global	Cat.1	●	●



## Specifications

### CELLULAR

AS700-LG (Global)	LTE FDD Cat.1 B1, B2, B3, B4, B5, B7, B8, B9, B12, B13, B14, B18, B19, B20, B25, B26, B28
Data Support	UDP / IP, TCP / IP
Antenna	Embedded cellular antenna

### POSITIONING

GNSS Receiver	99 channel engine
GNSS Engine	GPS & GLONASS
Other Location Technology	Wi-Fi Scan
SBAS Support	WAAS, EGNOS, GAGAN, MSAS
Tracking Sensitivity	-165dBm
Acquisition Sensitivity	-149dBm
Location Accuracy	2.5m CEP 50%
Antenna	Internal

### WIRELESS

Bluetooth	Low Energy v5.0, Class 2 (Support long range)
-----------	--

### SENSORS

Accelerometer	3-axis $\pm 16g$
Tamper Detection	Support
Bluetooth Sensor	Support BL1 Door Open Detection* Support BL1 Temperature Sensor* Support BL1 Humidity Sensor* Support BL1 Angle Sensor*

### ELECTRICAL

Operating Voltage	3.7V
Current Consumption	Deep Sleep Mode $< 22 \mu A$
Battery Life (without charging)	8 years (daily report interval) 6 months (hourly report interval) 1 months (every 10mins report interval)
Battery Capacity	8000mAh
LED Indicator	Internal in x1 (Battery Level Indicator) External in x1 (Operating Indicator)

### INPUTS/OUTPUTS (AS700-LGCSE-AT02 Only)

Input	1-Wire Interface**
Digital Output	250mA (max. sink current)

### POWER SOURCE (AS700-LGCSB-AT02 Only)

Solar Powered	1.7W High efficiency solar cell
---------------	---------------------------------

### MEMORY

Internal Flash Memory	16 Mbits
-----------------------	----------

### ENVIRONMENTAL

Operating Temperature	-40°C to +80 °C (Recharge -20°C to +50 °C)
Humidity	95%RH @ 50° C non-condensing
Vibration/Shock	MIL-STD-810H
Salt Fog	MIL-STD-810H
Unit Drop Test	MIL-STD-810H
Impact Resistance	IEC 62262 (IK10)
IP Rating	IP68, IP69K

### PHYSICAL

Dimension	216 mm x 89 mm x 30 mm (8.50" x 3.50" x 1.18")
Weight	500g (1.1lb) (For AS700-LGCSB-AT02) 540g (1.2lb) (For AS700-LGCSE-AT02)
Enclosure	UV-Resistant PC
Mounting Method	Screw Mount, Bolts

### CONNECTORS

SIM Card Socket	Mini SIM (2FF), e-SIM
USB-Type C	Battery recharge and configuration

### CONFIGURATION

Firmware Update	ADM (ATrack Device Management) by Bluetooth/USB-Type C
Configuration Update	ADM (ATrack Device Management) by Bluetooth/USB-Type C

### CERTIFICATIONS

Standards	FCC, IC, CE, RoHS, TELEC
-----------	--------------------------

\* Optional Accessories Required

\*\* Configurable

Last updated: 9-May-2024